

**Description:**

Marine teak treatment for timber protection.

**Intended use:**

Cyndan **Timber Protection Solution** is ideal for all natural timbers and is especially suited for application to Teak used in a marine environment.

**Features & Benefits:**

Forms a protective water resistant barrier. 18 month protection while reducing UV degradation. Natural low sheen finish.

**Limitations:**

Non defined.

**Sizes:**

5L, 25L, 205L, 1000L.

**Dilution:**

Apply neat.

**Clean up:**

Clean equipment with Xylene.

**Typical Physical Properties:**

<b>Appearance &amp; Odour</b>	Clear slightly coloured liquid.
<b>Melting/Softening Point</b>	No specific data. Liquid at normal temperatures.
<b>Boiling Point &amp; Vapour Pressure</b>	Boils in a range 145-190°C at 100kPa
<b>Volatile Materials</b>	Solvent Component.
<b>Flashpoint</b>	31°C, Approx.
<b>Specific Gravity</b>	Expected to be about 0.85
<b>Solubility in Water</b>	Completely insoluble
<b>Corrosiveness</b>	Non corrosive
<b>Shelf Life</b>	3 years after manufacture date

**Identification:**

<b>UN No.</b>	None Allocated
<b>Dangerous Goods Class</b>	None Allocated
<b>Hazchem Code</b>	None Allocated
<b>Sub Risk Class</b>	None Allocated
<b>Packaging Group</b>	None Allocated
<b>Poison Schedule</b>	Not Scheduled

**Application Instructions:**

**Protection**

Tests have shown outstanding protection over 18 months. Light sanding and a reapplication restore previously protected timber to its original condition. The protection process begins with the before mentioned preparation step. The best application procedure is to apply liberal amounts of **Timber Protection Solution** by spray or brush and then work it into the timber with a rag. Any excess can be removed with a dry rag, after allowing 10 to 20 minutes for the product to penetrate.

**Coverage**

Depending on the condition of the timber you may use up to 1 litre per 8 square metres. A second application on dry timber may be advisable. The resultant finish is a natural low sheen, non slip, beautifully toned timber. Storage and shelf life – store in original containers and reseal container after use. Store away from direct sunlight and extreme temperatures. Do not allow freezing, do not expose to temperatures above 50°C. Shelf life if stored in accordance with storage instructions – 12 months.

**Safety & References:**

Please see **MSDS (Material Safety Data Sheet)** for storage, safety and first aid directions before use. Please visit [www.cyndan.com.au](http://www.cyndan.com.au) for references for **Timber Protection Solution**.