

SAFETY DATA SHEET

Eco-Shield Eco-Solv ES36

Product Code : ES36

Version No: 1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 22/02/2023

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name: Eco-Shield Eco-Solv ES36

Chemical Name:

Synonyms:

Not Available

Other means of identification: Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Solvent

Details of the manufacturer or supplier of the safety data sheet

Supplier name LEFT PILLAR PTY LTD TA'S SHIELD CHEMICALS
Address Unit 7/37 Anzac Avenue Smeaton Grange, Sydney, NSW, 2567, AUSTRALIA
Telephone 1300 519 074
Email info@krystalshield.com.au
Website www.krystalshield.com.au
Emergency telephone numbers
Emergency 1300 519 074

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Not Applicable

Label elements

Hazard pictogram(s)

Not Applicable

Signal word: Not Applicable

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available	100	Oleochemical

SECTION 4 First aid measures

Description of first aid measures

Eye Contact

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

Inhalation

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

Ingestion

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- **DO NOT** approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

Fire/Explosion Hazard

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include:

carbon dioxide (CO₂)

acrolein

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

HAZCHEM

Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

- Remove all ignition sources.

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

Major Spills

CARE: Absorbent materials wetted with occluded oil must be moistened with water as they may auto-oxidize, become self heating and ignite.

Some oils slowly oxidise when spread in a film and oil on cloths, mops, absorbents may autoxidise and generate heat, smoulder, ignite and burn. In the workplace oily rags should be collected and immersed in water.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling

Rags wet / soaked with unsaturated hydrocarbons / drying oils may auto-oxidise; generate heat and, in-time, smoulder and ignite. This is especially the case where oil-soaked materials are folded, bunched, compressed, or piled together - this allows the heat to accumulate or even accelerate the reaction

Oily cleaning rags should be collected regularly and immersed in water, or spread to dry in safe-place away from direct sunlight or stored, immersed, in solvents in suitably closed containers.

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- **DO NOT enter confined spaces until atmosphere has been checked.**
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, **DO NOT eat, drink or smoke.**
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

Other information

Consider storage under inert gas.

Store in the dark.

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

Vegetable oils and some animal fats undergo undesirable deterioration reactions in the presence of oxygen from the air becoming rancid accompanying off-flavours and smells.

The mechanism of autoxidation of vegetable oils is classically regarded as following a number of stages being:

- a usually slow initiation phase
- a usually rapid propagation
- and a termination phase

The initiation phase involves the formation of a free radical from a triglyceride molecule in the fat: this may be promoted by the presence of heavy metals in the oil, or by heat or light.

The next stage is the reaction of the triglyceride free radical with oxygen to produce a peroxide free radical, which can react with another triglyceride to produce a hydroperoxide and another triglyceride free radical. Steps 2 and 3 can repeat in a chain reaction until two peroxy free radicals collide and neutralise each other.

Some drying oils produce cyclic peroxides instead of hydroperoxides.

Autooxidation may also occur in saturated fatty acids and their esters. Monohydroperoxides are formed. Although all carbon atoms are subject to oxidation, preferential oxidation appears to occur towards the centre of the molecule.

Autoxidation is assisted by higher ambient temperatures (the rate doubling for every ten degrees Centigrade rise) and by the presence of heavy metal ions, especially copper. The degree of unsaturation of the oil is also relevant to shelf-life; oils with a high linolenic fatty acid content (3 double bonds) being more prone than those with a higher saturated fatty acid content. Autoxidation can be minimized by the presence of anti-oxidants, which can act as free-radical inhibitors. Vegetable oils should therefore be stored in a cool place away from

heat and light, and should only come into contact with inert (glass of stainless steel) containers which will not leach heavy metals. Blanketing under nitrogen should be considered in bulk storages.

- Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

Exposure controls

Appropriate engineering controls

Care: Atmospheres in bulk storages and even apparently empty tanks may be hazardous by oxygen depletion. Atmosphere must be checked before entry.

Requirements of State Authorities concerning conditions for tank entry must be met. Particularly with regard to training of crews for tank entry; work permits; sampling of atmosphere; provision of rescue harness and protective gear as needed

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment



Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.

· Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- Excellent when breakthrough time > 480 min
- Good when breakthrough time > 20 min
- Fair when breakthrough time < 20 min
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- Neoprene gloves
- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

Body protection

See Other protection below

Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

SECTION 9 Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

:

Air sensitive.

Light sensitive.

Physical state	Liquid	Relative density (Water = 1)	0.86 - 0.90
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	<0	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	> 250	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>170	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available

Eco-Shield Eco-Solv ES36

Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	0
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity:

See section 7

Chemical stability :

- Unstable in the presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Possibility of hazardous reactions :

See section 7

Conditions to avoid :

See section 7

Incompatible materials :

See section 7

Hazardous decomposition products :

See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

The material has **NOT** been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence. In the absence of such evidence, care should be taken nevertheless to ensure exposure is kept to a minimum and that suitable control measures be used, in an occupational setting to control vapours, fumes and aerosols.

Inhalation hazard is increased at higher temperatures.

Inhalation of oil droplets/ aerosols may cause discomfort and may produce chemical pneumonitis.

Fine mists generated from plant/ vegetable (or more rarely from animal) oils may be hazardous. Extreme heating for prolonged periods, at high temperatures, may generate breakdown products which include acrolein and acrolein-like substances.

Ingestion

Fatty acid esters are relatively non-toxic in rats. Large doses of 20-60 gm/kg are lethal in rats.

The material has **NOT** been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Skin Contact

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Eye

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.

Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

The liquid is discomforting to the eyes

Chronic

Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Eco-Shield Eco-Solv ES36	TOXICITY	IRRITATION
	Not Available	Not Available

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Eco-Shield Eco-Solv ES36

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

Group A aliphatic monoesters (fatty acid esters) According to a classification scheme described by the American Chemistry Council Aliphatic Esters Panel, Group A substances are simple monoesters derived from a monofunctional alcohol, such as 2-ethylhexyl alcohol (C8-alcohol) or tridecyl alcohol (C13 alcohol) and fatty acids such as palmitic, stearic, oleic or linoleic acid. Metabolism of the parent esters is expected to yield the corresponding fatty acids and alcohols. The fatty acids are naturally occurring and have a low order of toxicity. Group A substances are rather lipophilic (log Kow 10-15) in character due to the large number of carbon numbers in the ester molecule (e.g., 24,26, 31 carbons) and have relatively high boiling points. Owing to the non-volatile nature of these esters, their vapour pressures are very low and difficult to determine experimentally. Water solubility is also very low. Mammalian Toxicity: Acute Toxicity. Many higher fatty acid esters, such as the stearates, oleates and palmitates, have been cleared for use in the food industry; thus, their general physiological response and toxicity are very low. Many of the higher fatty acid esters are considered safe for use in cosmetics. Available acute toxicity data indicate that the fatty acid esters in Group A, in general, have a low order of toxicity [e.g., palmitic acid, 2-ethylhexyl ester (LD50 > 5 g/kg) and tall oil fatty acid 2-ethylhexyl ester (LD50 > 64 g/kg)]. Consistent with that, available data spanning the carbon range of C22 to C34 indicate that the alkyl fatty acid esters are not toxic by oral administration [rat LD50 (oral) > 5g/kg, with range from 5 g/kg to 64 g/kg]. Butyl stearate is tolerated by rats without lethal effects at oral doses of 32 g/kg while octyl oleate has a reported LD50 of >40 ml/kg. In addition, many alkyl fatty acid esters, such as the stearates, oleates and palmitates, have been demonstrated to be not toxic by dermal administration. Because of the low volatility of these substances, inhalation exposure at toxicological significant levels is not expected. Repeated Dose Toxicity. 28-Day oral gavage studies in rats with decyl oleate (CAS 3687-46-5) at doses of 100,500 and 1000 mg/kg showed no toxicity as noted with respect to clinical symptoms, biochemistry, hematology, gross lesions or tissue/organ histopathology. The NOEL was estimated to be 1000 mg/kg. Similarly, octyl or (2-ethylhexyl) stearate showed a NOEL of 1000 mg/kg in 28-day oral gavage studies in rats. In chronic two-year feeding studies with butyl stearate at concentrations of 1.25% or 6.25% in the diet, exposed rats showed no significant difference from control animals with respect to growth, survival, blood counts or other haematological parameters. Besides the two substances above, various other long-chain fatty acid esters have also been studied for their repeated dose toxicity and the findings support a low order of toxicity. Genotoxicity: Genetic Toxicity (Salmonella). Fatty acid, C 16- 18 saturated and C 18 unsaturated, 2-ethylhexanoate (CAS 85049-37-2); octyl stearate (CAS 109-36-4); and decyl oleate (CAS 3687-46-5) were shown to be negative in the Ames assay. Since the monoesters are similar in chemical structure and carbon-number range, it is unlikely that esters in Group A will induce point mutation. In addition, the chemistry of the long-chain fatty acids does not suggest the likelihood that these substances or their constituent substructures (i.e., fatty acids, alcohols) are reactive or electrophilic in nature. Genetic Toxicity (Chromosomal Aberrations). The chemistry of the long-chain fatty acid esters does not suggest the likelihood that these substances or their constituent substructures (i.e., fatty acids, alcohols) are reactive or electrophilic in nature. Therefore, the likelihood that the fatty acid monoesters may cause chromosomal mutation is very low. Reproductive toxicity: Assessment of reproductive effects of alkyl fatty acid esters in Group A is based primarily on studies with butyl stearate. Fertility, litter size and survival of offspring were normal in rats fed diets containing 6.25% butyl stearate for 10 weeks. However, growth was reduced in offspring during the pre-weaning and post-weaning periods. No gross lesions were noted among the offspring killed at the end of the 21-day post-weaning periods. These results indicate that long-chain fatty acid esters do not cause reproductive toxicity in rats. Given the relative low order of toxicity for long-chain fatty acid esters and their relative non-electrophilic and non-reactive nature, it seems unlikely that the long-chain fatty acid esters would present serious reproductive concerns. Developmental Toxicity/ Teratogenicity. Assessment of developmental effects for the long-chain fatty acid esters in this group was based primarily on data reported for fatty acid, C16-18, 2-ethylhexyl ester (CAS 91031-48-0). In oral gavage studies in rats administered doses of 100,300 and 1000 mg/kg during gestation, the maternal NOEL was > 1000 mg/kg and the NOEL for teratogenicity was >1000 mg/kg. Based on these findings and the fact Group A substances, are very chemically similar to the structure of the tested material, read-across assessment is thought to be appropriate.

For aliphatic fatty acids (and salts)

Acute oral (gavage) toxicity:

The acute oral LD50 values in rats for both were greater than >2000 mg/kg bw. Clinical signs were generally associated with poor condition following administration of high doses (salivation, diarrhoea, staining, piloerection and lethargy). There were no adverse effects on body weight in any study. In some studies, excess test substance and/or irritation in the gastrointestinal tract was observed at necropsy.

Skin and eye irritation potential, with a few stated exceptions, is chain length dependent and decreases with increasing chain length.

According to several OECD test regimes the animal skin irritation studies indicate that the C6-10 aliphatic acids are severely irritating or corrosive, while the C12 aliphatic acid is irritating, and the C14-22 aliphatic acids generally are not irritating or mildly irritating.

Human skin irritation studies using more realistic exposures (30-minute, 1-hour or 24-hours) indicate that the aliphatic acids have sufficient, good or very good skin compatibility.

Animal eye irritation studies indicate that among the aliphatic acids, the C8-12 aliphatic acids are irritating to the eye while the C14-22 aliphatic acids are not irritating.

Eye irritation potential of the ammonium salts does not follow chain length dependence; the C18 ammonium salts are corrosive to the eyes.

Dermal absorption:

The in vitro penetration of C10, C12, C14, C16 and C18 fatty acids (as sodium salt solutions) through rat skin decreases with increasing chain length. At 86.73 ug C16/cm² and 91.84 ug C18/cm², about 0.23% and less than 0.1% of the C16 and C18 soap solutions is absorbed after 24 h exposure, respectively.

Sensitisation:

No sensitisation data were located.

Repeat dose toxicity:

Repeated dose oral (gavage or diet) exposure to aliphatic acids did not result in systemic toxicity with NOELs greater than the limit dose of 1000 mg/kg bw. .

Mutagenicity

Aliphatic acids do not appear to be mutagenic or clastogenic in vitro or in vivo

Carcinogenicity

No data were located for carcinogenicity of aliphatic fatty acids.

Reproductive toxicity

No effects on fertility or on reproductive organs, or developmental effects were observed in studies on aliphatic acids and the NOELs correspond to the maximum dose tested. The weight of evidence supports the lack of reproductive and developmental toxicity potential of the aliphatic acids category.

Given the large number of substances in this category, their closely related chemical structure, expected trends in physical chemical properties, and similarity of toxicokinetic properties, both mammalian and aquatic endpoints were filled using read-across to the closest structural analogue, and selecting the most conservative supporting substance effect level.

Structure-activity relationships are not evident for the mammalian toxicity endpoints. That is, the low mammalian toxicity of this category of substances limits the ability to discern structural effects on biological activity. Regardless, the closest structural analogue with the most conservative effect value was selected for read across. Irritation is observed for chain lengths up to a cut-off¹ at or near 12 carbons).

Metabolism:

The aliphatic acids share a common degradation pathway in which they are metabolized to acetyl-CoA or other key metabolites in all living systems. Common biological pathways result in structurally similar breakdown products, and are, together with the physico-chemical properties, responsible for similar environmental behavior and essentially identical hazard profiles with regard to human health.

Differences in metabolism or biodegradability of even and odd numbered carbon chain compounds or saturated/ unsaturated compounds are not expected; even-and odd-numbered carbon chain compounds, and the saturated and unsaturated compounds are naturally occurring and are expected to be metabolized and biodegraded in the same manner.

The acid and alkali salt forms of the homologous aliphatic acid are expected to have many similar physicochemical and toxicological properties when they become bioavailable; therefore, data read across is used for those instances where data are available for the acid form but not the salt, and vice versa. In the gastrointestinal tract, acids and bases are absorbed in the undissociated (non-ionised) form by simple diffusion or by facilitated diffusion. It is expected that both the acids and the salts will be present in (or converted to) the acid form in the stomach. This means that for both aliphatic acid or aliphatic acid salt, the same compounds eventually enter the small intestine, where equilibrium, as a result of increased pH, will shift towards dissociation (ionised form).

Hence, the situation will be similar for compounds originating from acids and therefore no differences in uptake are anticipated

Note that the saturation or unsaturation level is not a factor in the toxicity of these substances and is not a critical component of the read across process..

Toxicokinetics:

The turnover of the [14C] surfactants in the rat showed that there was no significant difference in the rate or route of excretion of 14C given by intraperitoneal or subcutaneous

administration. The main route of excretion was as 14CO_2 in the expired air at 6 h after administration. The remaining material was incorporated in the body. Longer fatty acid chains are more readily incorporated than shorter chains. At ca. 1.55 and 1.64 mg/kg bw, 71% of the C16:0 and 56% of the C18:0 was incorporated and 21% and 38% was excreted as 14CO_2 , respectively.

Glycidyl fatty acid esters (GEs), one of the main contaminants in processed oils, are mainly formed during the deodorisation step in the refining process of edible oils and therefore occur in almost all refined edible oils. GEs are potential carcinogens, due to the fact that they readily hydrolyze into the free form glycidol in the gastrointestinal tract, which has been found to induce tumours in various rat tissues. Therefore, significant effort has been devoted to inhibit and eliminate the formation of GEs

GEs contain a common terminal epoxide group but exhibit different fatty acid compositions. This class of compounds has been reported in edible oils after overestimation of 3-monochloropropane-1,2-diol (3-MCPD) fatty acid esters analysed by an indirect method, 3-MCPD esters have been studied as food processing contaminants and are found in various food types and food ingredients, particularly in refined edible oils. 3-Monochloropropane-1,2-diol (3-MCPD) and 2-monochloropropane-1,3-diol (2-MCPD) are chlorinated derivatives of glycerol (1,2,3-propanetriol). 3- and 2-MCPD and their fatty acid esters are among non-volatile chloropropanols. Glycidol is associated with the formation and decomposition of 3- and 2-MCPD. It forms monoesters with fatty acids (GE) during the refining of vegetable oils. Chloropropanols are formed in HVP during the hydrochloric acid-mediated hydrolysis step of the manufacturing process. In food production, chloropropanols form from the reaction of endogenous or added chloride with glycerol or acylglycerol. Although harmful effects on humans and animals have not been demonstrated, the corresponding hydrolysates, 3-MCPD and glycidol, have been identified as rodent genotoxic carcinogens, ultimately resulting in the formation of kidney tumours (3-MCPD) and tumours at other tissue sites (glycidol). Therefore, 3-MCPD and glycidol have been categorised as "possible human carcinogens (group 2B) and "probably carcinogenic to humans (group 2A), respectively, by the International Agency for Research on Cancer (IARC). Diacylglyceride (DAG) based oils produced by one company were banned from the global market due to "high levels" of GEs.

Several reports have also suggested that a bidirectional transformation process may occur not only between glycidol and 3-MCPD but also their esterified forms in the presence of chloride ions. The transformation rate of glycidol to 3-MCPD was higher than that of 3-MCPD to glycidol under acidic conditions in the presence of chloride ion. Precursors of GEs in refined oils have been identified as partial acylglycerols, that is, DAGs and monoacylglycerides (MAGs); however, whether they also originate from triacylglycerides (TAGs) is still a topic of controversial debates. Several authors noted that pure TAGs were stable during heat treatment (such as 235 deg C) for 3 h and were therefore not involved in the formation of GEs. However, experimental results have shown that small amounts of GEs are present in a heat-treated oil model consisting of almost 100% TAGs. The formation of GEs from TAGs can be attributed to the pyrolysis of TAGs to DAGs and MAGs. In contrast, 3-MCPD esters in refined oils can be obtained from TAG. Presently, the mechanism for the formation of GE intermediates and the relationship between GEs and 3-MCPD esters are still unknown.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend:

- ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information**Toxicity**

Eco-Shield Eco-Solv ES36	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For aliphatic fatty acids and alcohols:

Environmental fate:

Saturated fatty acids are very stable in air, whereas unsaturated (C=C bonds) fatty acids are susceptible to oxidation.

Unsaturation increases the rate of metabolism although the degree of unsaturation and positioning of double bonds is not highly significant.

The available data indicate all fatty acid salt chain lengths up to and including C18 can be metabolised under aerobic conditions and can be considered to be readily biodegradable

All tests showed that fatty acids and lipids are readily biodegradable

The aliphatic acids are of similar very weak acid strength (approximately pKa 5), i.e., partially dissociate in aqueous solution; the salts of the aliphatic acids are highly dissociated in water solution such that the anion is the same for homologous salts and acids.

Slight (although inconsistent) effects on the trend for decreasing vapour pressure are also observed with the mono-, di- and tri-unsaturated substances as compared to the corresponding saturated substances.

Dicarboxylic acids: Compared to their corresponding single acid substances (C8-10 single component, saturated), the dicarboxylic acids exhibit modestly higher melting/ boiling points and water solubility, and lower partition coefficients and vapour pressures. The trends described above for changes in physical chemical properties with increasing carbon chain length apply.

Salts: As expected, the salts differ in physical / chemical properties as compared to their homologous single component substances. However the trends described above for single components with regard to changes in physical chemical properties with increasing carbon chain length apply

Models also indicate that the aliphatic acids will distribute primarily to soil and water, with lesser amounts to air and sediment. With increasing chain length, the percent distributions to soil and sediment generally increase and the percent distributions to water and air generally decrease.

The rate of degradation of fatty acids was investigated in two non-GLP studies.

The total fatty acids residue exhibits low persistence in soil. From the pattern of peaks decline, it was hypothesised a degradation pathway by the sequential elimination of C2 fragments. Consequently, the major soil metabolites of a given fatty acid would be other fatty acids with shorter chains.

Although mineralisation was not measured in these experiments, formation of CO_2 is the expected terminal step of this process. Fatty acids undergo aerobic biodegradation by the process of beta-oxidation. Beta-oxidation of the parent fatty acid forms acetate and a new fatty acid of two less carbon atoms. This process repeats itself until the compound is completely broken down. The hydrocarbon will eventually be degraded to CO_2 and H_2O . For this reason, the length of the fatty acid chain does not preclude biodegradation, but it may take longer to achieve complete mineralisation. The beta-oxidation sequence does not necessarily require the presence of molecular oxygen, and fatty acid biodegradation may proceed under anaerobic conditions.

Hydrolysis is not an important fate path in the environment due to the fact that the substances lack hydrolysable functional groups. Aliphatic acids are hydrolytically stable in aqueous solution.

Water solubility:

In general, the water solubility of single carbon chain length substances followed a pattern of decreasing solubility as carbon chain length increases, especially at C16 and higher.

In addition, greater solubility is seen for dicarboxylic acids as compared to their homologous single acids:

In reviewing the physical/ chemical properties of the a.aliphatic acids, two predominant trends are clearly evident with increasing alkyl chain length and include: i) increasing melting point, boiling point, and partition coefficient, and ii) decreasing water solubility and vapour pressure. Within a given carbon chain length, melting point increases with increasing saturation and decreases with increasing unsaturation. The noted general trends with increasing alkyl chain length are observed when an entire single component group (12 saturated, 4 mono-unsaturated, 2 di-unsaturated, and 1 tri-unsaturated substances) is evaluated together; that is the degree of saturation or unsaturation does not alter the properties trend The effect of mono-unsaturation (C14:1 to C22:1) appears to be a slight increase in water solubility and a slight decrease in the partition coefficient, as compared to the corresponding saturated substances; a similar trend is noted for the C18 di- or tri-unsaturated substances.

Fatty acids (including methyl esters) were stable to hydrolysis in the pH range of 1-14. It is not expected that photolysis would significantly contribute to the degradation of fatty acids in water.

According to modelling, the aliphatic acids are subject to photodegradation in air. Estimated half-lives generally increase with decreasing chain length and range from 0.6 hours to 17.5 hours.

Methyl (and other) esters are estimated to exhibit high mobility and the acids very high mobility. Mobility may be expected to be higher for the salts than for the corresponding acids and methyl esters

Biodegradation studies or model estimations for single and multi-component aliphatic acids generally confirm that the extent of biodegradation observed in 28 days meets the ready biodegradability criterion (>60%). When the 10-day window was not met or less than 60%, biodegradation was observed in 28 days, it is likely that the aliphatic acids tested were not fully in solution.

Biodegradability tests demonstrated that pelargonic acid (C9), potassium salts and methyl octanoate / methyl decanoate are readily biodegradable. It can be assumed that both acids and methyl esters fatty acids C7-C18 are readily biodegradable.

No experimental bioaccumulation data appear to be available but log Kow data from various sources are higher than 4, which indicates that fatty acids and natural lipids have a potential for bioaccumulating in aquatic organisms.

Fatty alcohols up to chain length C18 are biodegradable, with length up to C16 biodegrading within 10 days completely. Chains C16 to C18 were found to biodegrade from 62% to 76% in 10 days. Chains greater than C18 were found to degrade by 37% in 10 days. Field studies at waste-water treatment plants have shown that 99% of fatty alcohols lengths C12-C18 are removed.

A review of soaps (including calcium and magnesium salts) states that the available data indicate all fatty acid salt chain lengths up to and including C18 can be metabolised under aerobic conditions and can be considered to be biodegradable. Biodegradability did not appear to be influenced by even or odd chain length, degree of saturation or unsaturation or branching. For example odd/even chain length C8 and C9 are readily biodegradable; Saturation/unsaturation: C18(saturated) and C18 (di-unsaturated) are biodegradable, while C18 (mono-unsaturated) are readily biodegradable; branching or hydroxylation: the C18 hydroxylated substance was readily biodegradable and the C18 methyl branched substance was biodegradable.

Higher water solubility of the potassium, sodium and ammonium salts make these a lower ranked analogy for the aquatic toxicity endpoints for the (non-salt) aliphatic acids (and vice versa), while lower water solubility of the magnesium and calcium salts make these a lower ranked analogy for all other members of the category

The aliphatic acids also undergo biodegradation under anaerobic conditions.

Estimated bioconcentration factor values are calculated using EPI Suite v4.10. The aliphatic acids have BCF values less than 100, indicating a low potential for bioaccumulation

Fate prediction using fugacity modeling has shown that fatty alcohols with chain lengths of C10 and greater in water partition into sediment. Lengths C14 and above are predicted to stay in the air upon release. Modeling shows that each type of fatty alcohol will respond independently upon environmental release

Ecotoxicity

Structure-activity relationships based on carbon chain length are evident in the available data on the aquatic ecotoxicity of substances of this category (aquatic toxicity increases with increasing chain length up to a "cutoff" at or near 12 carbons).

The aliphatic acids category members possess properties indicating a hazard for the environment (acute toxicity to fish: between 1-100 mg/L for carbon chain lengths C6 through C12, and multi-component sodium or potassium salts C16-18; acute toxicity to aquatic invertebrates: between 1 and 100 mg/L for carbon chain lengths C6 through C9 (including sodium salts) and less than 1 mg/L for sodium salts single component aliphatic acids C18 and multi component sodium salt aliphatic acids with carbon chain lengths including C14 through C18; and, acute toxicity to aquatic plants: between 1-100 mg/L for carbon chain length C12, including sodium or ammonium salts).

There are a number of acute data for fatty acids and fatty acid salts to aquatic organisms although there is a predominance of data for fatty acid. There are few toxicity values for terrestrial organisms. Data availability / quality covering all the taxonomic groups for specific fatty acid salt chain lengths is poor. The chronic data set is very limited.

For chain lengths >C12, solubility decreases to a degree where an adverse effect would not be expected in the environment due to reduced bioavailability. Data for longer chain lengths have been generated using solvents which makes interpretation more difficult.

The most of few available data indicate low toxicity towards aquatic organisms with EC/LC50 values above 1000 mg/l. However, EC/LC50 values below 100 mg/l are not unusual either

Fish, invertebrates and algae experience similar levels of toxicity with fatty alcohols although it is dependent on chain length with the shorter chain having greater toxicity potential.

Longer chain lengths show no toxicity to aquatic organisms.

The available toxicity data indicated low acute and short-term (for birds only) toxicity to birds and mammals. Given that fatty acids are an essential component of the diet of birds and mammals a low risk is expected. On the basis that fatty acids are readily biodegradable and are an essential component of the diet of birds and mammals, a low reproductive risk is expected.

No toxicity data were available for higher aquatic plants and therefore a risk assessment cannot be performed. As pelargonic acid, fatty acid/salt and C8-C10 methyl esters are used as herbicides and plant growth regulators, a data gap to address the risk to higher aquatic plants was identified

A low risk to natural populations of bees and non-target arthropods was concluded for representative greenhouses uses of potassium salts of fatty acids, fatty acid/salt and C8-C10 methyl esters.

Given that fatty acids are readily biodegradable a low risk to sewage treatment organisms was concluded for all of the representative uses.

For Group A aliphatic esters (fatty acid esters):

Environmental fate:

Group A substances are rather lipophilic (log Kow 10-15) in character due to the large number of carbons in the ester molecule (e.g., 24,26, 31 carbons) and have relatively high boiling points. Owing to the non-volatile nature of these esters, their vapor pressures are very low and difficult to determine experimentally. Water solubility is also very low.

Hydrolysis half lives and atmospheric photodegradation rates were calculated by EPIWIN. The monoester hydrolysis rates were determined to be quite low and not a significant environmental fate route. Fugacity modeling indicates that the fatty acid esters have similar distribution patterns in the environmental compartments (e.g., air, water, soil, sediment).

Biodegradation of alkyl fatty acid esters are expected to occur extensively based on the reported 28 day test results (80-85% biodegradation, OECD 301D) for decyl oleate and for the 2-ethylhexyl ester of C16- 18 saturated and C18 unsaturated fatty acids (CAS 85049-37-2). Group A Substances are expected to be extensively biodegraded since the fatty acids in these esters are primarily comprised of palmitic, stearic or oleic acids, which are known to be rapidly biodegraded

Ecotoxicity:

Aquatic toxicity results have been reported for decyl oleate and fatty acid, C16- 18 saturated and C18 unsaturated, 2-ethylhexanoate They are not acutely toxic to fish (LC50 3200 mg/L). In daphnids, the acute LC50 was reported to be 17 mg/L and in algae, the LC50 was reported to be 40-42 mg/L based on biomass and growth rate endpoints. Because of their limited water solubility, the alkyl fatty acid esters and Group A esters are not likely to cause acute aquatic toxicity.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- **DO NOT allow wash water from cleaning or process equipment to enter drains.**
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant

NO

HAZCHEM

Not Applicable

	Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS	Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS	Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS
UN number: Not Applicable			
UN proper shipping name: Not Applicable			
Transport hazard class(es): Not Applicable			
Subrisk: Not Applicable			
Packing group: Not Applicable			

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Oleochemical	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Oleochemical	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (Oleochemical)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date: 22/02/2023

Continued...

Initial Date: 22/02/2023

CONTACT POINT

IMMEDIATELY contact the local POISON CONTROL center for your area (24 hours): Alberta 1-800-332-1414 British Columbia 1-800-567-8911 Manitoba 1-855-776-4766 New Brunswick 911 Newfoundland and Labrador 1-866-727-1110 Northwest Territories 1-800-332-1414 Nova Scotia and Prince Edward Island 1-800-565-8161, 1-800-332-1414 or 911 Nunavut 1-800-268-9017 Ontario 1-800-268-9017 Quebec 1-800-463-5060 Saskatchewan 1-866-454-1212 Yukon Territory 867-393-8700 United States 1-800-222-1222 Contactez IMMÉDIATEMENT le centre ANTIPOISON de votre région (24 heures): Alberta 1-800-332-1414 Colombie-Britannique 1-800-567-8911 Manitoba 1-855-776-4766 Nouveau-Brunswick 911 Terre-Neuve-et-Labrador 1-866-727-1110 Territoires du Nord-Ouest 1-800-332-1414 Nouvelle-Écosse et Île-du-Prince-Édouard 1-800-565-8161, 1-800-332-1414 ou 911 Nunavut 1-800-268-9017 Ontario 1-800-268-9017 Québec 1-800-463-5060 Saskatchewan 1-866-454-1212 Territoire du Yukon 867-393-8700 États-Unis: 1-800-222-1222

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
ES: Exposure Standard
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index
AIIIC: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.